

Brute[®] 2-CL Servo Drive Label Applicator



Hunkar Packaging **Brute[®] 2-CL** with No-stall Servo Motor Drive technology is the most reliable, low maintenance modular label applicators available with 24/7 durability. It is a favorite in the dairy industry since its inception at Lord Label Machinery. The modular design and construction provide simple adaptation for applications including left or right hand label installation, Roll-On, Tamp, Blow-On, and Corner Wrap, Hinge Tamp, Side or Top Apply configurations.

FEATURES:

- **No-Stall Servo Motor Drive Technology**
- **Digital Controls for Precise Parameter Stability**
- **On Board Memory for 10 Label Parameter Recall**
- **Easy to Use 4-Button Operator Interface**

Specifications:

- Anodized aluminum construction with stainless steel fasteners.
- Approximate weight of applicator with controls is 95 lbs. (43kg)
- Brushless DC drive system with encoder (servo motor)
- Designed for continuous operation up to 1200 inches/min. (3048 cm/min.)
- Microprocessor controller for high visibility in any lighting condition.
- 115 Volt AC, single phase, 50/60 Hz, 8 amp, true earth ground
- Operating temperature range; 40° F to 125° F (4.4 ° C to 51.6 ° C)
- Available in right or left hand configuration
- User friendly electronic controls with programmable presets

Option

- Structural Steel tri-base with corrosion resistant powder coat finish
- Clear label sensor
- Hot stamp imprinters
- Supply roll size: 16" O.D.
- Low label detection system
- Alarm light tree
- Product handling equipment

Label

- Standard 4" with optional oversize web widths including 6", 8", 10", 12"
- Core size: 3" I.D.
- Die-cut, edge trimmed and waste removed with minimum 3/32" gap
- 12" Supply roll
- Opaque label